

Alcon Smart Surveillance Express V8.2





OVERVIEW

Alcon Smart Surveillance Express is an independent video management software based for macOS (64bits) and Windows (64bits) Operation system for Alcon IP cameras, PTZs, NVRs, XVRs, decoders etc. Maximum 200 IP devices or 512 channels can be connected in Alcon Smart Surveillance Express. It supports functions like preview, playback, alarm, two-way audio, PTZ control etc. and configurations like device management, user management, storage, event etc.

Alcon Smart Surveillance provides multiple solutions like people counting solution, fever detection solution, face recognition solution for small and medium scenarios with friendly using experience and intuitive data report.



FEATURES

New UI interfaces

Supports Windows 7/10 64bits and macOS 64bits

Device management

- Search online devices and modify net information
- Supports thermal bullet camera to detect body temperature

Preview

- Supports 1/2/3/4/1-5/1-7/9/10/13/16/17/25/36/49/64 window division mode and customization of display split
- Supports cruising and cruising list
- Supports displaying face capture picture with face information
- Supports displaying face comparison result with face information

Playback

- Supports fast/slow forward, step forward
- Supports 1/2/3/4/9/16 window division mode
- Supports one-key to capture all channels

System Setting

- Supports data backup, recover, clear up and reindex
- Supports 17 languages including English, Simplified Chinese, Traditional Chinese, Russian, Korean, Thai, Vietnamese, Polish, French, Italian, Arabic, Turkish, Spanish, Dutch, Hebrew, Czech and Slovak
- Dark/light skins available
- Drag alarm type to set alarm grade
- Supports setting duration of face picture storage

Alarm

- Add new real-time alarm column, easy to check alarm message
- Supports history alarm search and export

Intelligent Search

• Search face pictures by filters like gender, age, wearing mask or not, wearing glasses or not or unacceptable body temperature

Statistics

- Supports face statistics in list or graphics
- Supports managing up to 64 people counting cameras in one zone and displaying real-time statistics
- Supports people counting statistics in list or graphics

P2P Function

- Add device via P2P
- Live view with audio and remote playback through P2P
- Switch P2P server region



	ALCON SMART SURVEILLANCE EXPRESS		
Supported Devices	IPC, NVR, XVR, PTZ etc.		
Max Connected Devices	200 IP devices or 512 channels		
	1. Switch between Chinese and English for installation		
System Framework	2. Common functions and basic functions		
	3. Drag to add new function icon or remove it		
	4. Drag to change function icon order		
	1. Create password when first start the software		
Login	2. Support forgot password by protection questions		
	 Auto login, remember password Support switching languages in login interface 		
	1. Add/delete/edit user and configure user authority		
User Management	2. Set period of validity		
	1. Auto search devices within same LAN, supports batch and one-key addition		
	2. Support manual addition by IP, DDNS, EasyDDNS, P2P (Only for Windows version)		
Device Management	3. Support group management		
Device Management	4. Support acquiring device channel name or sync channel name to devices		
	5. Support jumping to device IE interfaces in default browser		
	6. Support export and import of device and group organization list		
	 Support device list and device online status Support one-key to connect/disconnect all channels 		
	 Support one-key to connect all charmers Support 1/2/3/4/1-5/1-7/9/10/13/16/17/25/36/49/64 window division mode and customization of display split 		
	4. Support to enable/disable audio and two-way audio		
	5. Support capture and one-key to capture all channels		
Preview	6. Support to switch main and sub stream, set video parameters		
	7. Support record and one-key to record all channels		
	8. Support PTZ control, focus, aperture, preset, light/wiper control		
	9. Support saving view, view rotating and group switch		
	10. Support face capture and display body temperature info during preview		
	11. Support face recognition and display comparison result		
	 Support device list and device online status Playback control, play/pause/fast forward/slow forward/step forward 		
	3. Support 1/2/3/4/9/16 window division mode		
	4. Time line supports zoom in/out		
Playback	5. Support capture and one-key to capture all channels		
	6. Support to enable/disable audio		
	7. Search video by calendar, date, storage location, stream type, etc.		
	8. Download video clip by file or by time		
Operation Logs	1. Query operation logs by time, type, user, etc.		
	2. Export log information		
	1. Retrieve face pictures by time, gender, age, mask, glasses, body temperature		
Intelligent Search	2. Result can be displayed in list or figure		
	 Check detailed picture or video Export data 		
DATA STATISTICS	- Export data		
Face Statistics	Show face data statistics in list or graphics according to different filter		
	1. Manage up to 64 people counting camera in one zone and set configuration of people counting rule		
	2. Preview of people counting camera		
Visitor Flow Statistic	3. Display peak number, current number and line chart in real time		
	4. Support to set time duration of people counting, people capacity alarm, rapidly increased number alarm and number of		
	people stay 5. Show reported statistic in list or graphics according to different filter		
ALARM	5. Show reported statistic in list of graphics according to different litter		
	1. Real time alarm in Alarm Management, quick to play alarm video or real time video		
Dool Timo Alerm	2. Support alarm filter by alarm grade		
Real Time Alarm	3. Operator can handle and input comment to real time alarm		
	4. Turn on/off alarm audio of software		
	1. Query history alarm by time, source, status, user		
History Alarm	2. Support alarm filter by alarm grade		
	3. Operator can handle and input comment to history alarm		



SYSTEM CONFIGURA	ATION
Common Settings	 Set capture and download file path Automatic login Data backup/recover/clear up/re index (re index face capture and record) Change language and software skin 17 languages including English, Simplified Chinese, Traditional Chinese, Russian, Korean, Thai, Vietnamese, Polish, French, Italian, Arabic, Turkish, Spanish, Dutch, Hebrew, Czech and Slovak are supported Set save time of log and alarm log
Video	 Set stream switch by automatically or manually Set play strategy, good fluency or minimum delay Hardware decoding available for Windows version Set download format, SDV and MP4 are supported
Alarm Grade	Set alarm grade
Storage Management	1. Set recoding package time, format, stream type 2. Set space strategy, storage location
Intelligent Application	 Enable intelligent application to receive face capture pictures and face recognition results Set face picture save duration by day Check deletion strategy to set visitor flow statistic save duration by month
P2P Setting	Set P2P server region

		PERFORMANCE			
WINDOWS (DESKTOP)					
Spec		Live View	Main stream (ch)	Sub stream (ch)	
		1080P/H.264	20	70	
i5-8Generation 8G Memory Windows 10		1080P/H.265	20	70	
		1080P/S+265	25	70	
WINDOWS (LAPTOP)					
Spec	Mode	Live View	Main stream (ch)	Sub stream (ch)	
		1080P/S+265	5	50	
· = 0000110	CPU Mode GPU Mode	1080P/H.265	2	50	
i5-6300HQ		1080P/H.264	2	70	
8G Memory GTX960M Windows 10		1080P/S+265	9	75	
Windows to		1080P/H.265	9	75	
		1080P/H.264	9	75	
MACOS					
Spec		Live View	Main stream (ch)		
Mac Mini (i5-6core/8G)		1080P/H.265	9	9	
MacBook Pro (i5-4core/8G)		1080P/H.265	6		
iMac (i5-2core/8G)		1080P/H.265	8		
		CONNECTION PERFORM			
Device Type		Network	Chann	els Number	

Device Type	Network	Channels Number
Alcon Devices	LAN	512
Alcon P2P Devices	WAN	512

EXPORT PERFORMANCE OF FACE PICTURE				
Data	Windows	Mac Mini	MacBook	iMac
1 Day Per Channel	3s	<3s	<3s	<3s
1 Week Per Channel	10s	11s	7s	8s
1 Month Per Channel	48s	1'20"	19s	30s
3 Month Per Channel	30'7"	5'59"	1'27"	1'55"
91W Face Pictures	4h7min	40min	1h2min	1h19min

RECOMMENDED SYSTEM REQUIREMENT

OS	Windows7/window10/MacOS
CPU	i5-8Generation Minimum
Memory	16GB Minimum
HDD	512G or Better
Network Card	100/1000M Self Adaptive
GPU	GTX1050 4G or better
Display	1920*1080 or better



*Product specifications and availability are subject to change without notice.



in t f 😔